

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**


Ref 4  
G-44**OPERATION CONTROL DEVICE FOR FUEL CELL**

Patent number: JP2098063  
 Publication date: 1990-04-10  
 Inventor: NAKAJIMA NORIYUKI  
 Applicant: FUJI ELECTRIC CO LTD  
 Classification:  
 - international: H01M8/04  
 - european:  
 Application number: JP19880250153 19881004  
 Priority number(s):

**Abstract of JP2098063**

**PURPOSE:** To reduce the loss in a power converter by comparing the voltage of the transmission power after the start of the power generation with the desired voltage value at the start of the power-generation obtained from a memory, and controlling the cell temperature via a cooling medium in accordance with the deviation therebetween.

**CONSTITUTION:** The relation between the output voltage and the load current at the start of the power generation is stored in a memory 23. As to the transmission power after the start of the power generation, the output voltage at the start corresponding to the load current thereof is output from the memory 23 as a desired value, and this desired output voltage value and the output voltage at the transmission power are input to a temperature controller 24, and the rotating speed of a circulating fan 3 is controlled according to the deviation between these two voltages to control the cooling air flow rate and hence the cell temperature in a cell stack. In this case, the cooling air flow rate is controlled so that, after the start, the cell temperature is higher i.e., the cooling air flow rate is smaller than those at the start. Thus, even after the start, the high output voltage at the start can be maintained for the power, so that the set load power can be transmitted with a reduced load current.



Data supplied from the esp@cenet database - Worldwide

## **OPERATION CONTROL DEVICE FOR FUEL CELL**

Legal status (INPADOC) of **JP2098063**

**No legal data found.**

**RESULT LIST**

1 result found in the Worldwide database for:  
"JP2098063" as the publication number  
(Results are sorted by date of upload in database)

**1 OPERATION CONTROL DEVICE FOR FUEL CELL**

Inventor: NAKAJIMA NORIYUKI

Applicant: FUJI ELECTRIC CO LTD

EC: H01M8/04B2

IPC: H01M8/04

Publication info: JP2098063 - 1990-04-10

---

Data supplied from the *esp@cenet* database - Worldwide